

MATERIAL SAFETY DATA SHEET

ARCOT Manufacturing Corporation
2950 Mowery Road
Houston, Texas 77045-4809

Emergency Telephone:
(713) 413-9700
Date Prepared: 10/20/2008

| SECTION I | | | | |
|---|---|---|--------------------------|------------------|
| Product Identity (Name / Number) | | DEFOAM IT Defoamer / Antifoam # 9666 | | |
| Chemical Family | | Emulsion Blend | | |
| SECTION II - Hazardous Ingredients | | | | |
| Hazardous Components | OSHA PEL | ACGIH TLV | Other Limits Recommended | % (optional) |
| cis-1-(3-Choroallyl)-3,5,7-triaza-1-azoniaadamantane chloride | | 1mg/m ³ | | <1% |
| Hexamethylenetetramine | | | | <1% |
| | | | | |
| | | | | |
| | | | | |
| SECTION III - Physical & Chemical Characteristics | | | | |
| Boiling Point | Above 212°F | Specific Gravity | 1 | |
| Vapor Pressure (mm Hg) | N/A | Melting Point | N/A | |
| pH | 7 | Evaporation Rate (Ethyl Ether=1) | Less than 1 | |
| Solubility in Water | Dispersible | Appearance / Odor | White Emulsion / Mild | |
| SECTION IV - Fire & Explosion Hazard Data | | | | |
| Flammable Limits (Explosive Limit) | Upper: | N/A | Lower: | N/A |
| Flash Point (Method Used) | N/A | | | |
| Extinguishing Media | Material is nonflammable. Water spray, foam, carbon dioxide, or dry chemical may be used for surrounding fires | | | |
| Special Fire Fighting Procedures | Product is nonflammable. Wear self-contained breathing apparatus and full protective clothing. Contact surfaces will be slippery. | | | |
| Unusual Fire and Explosion Hazards | | | | |
| SECTION V - Reactivity Data | | | | |
| Stability: | Unstable | X | Stable | |
| Hazardous Polymerization: | X | Will Not Occur | | May Occur |
| Conditions To Avoid | Excessive heat. Freezing. | | | |
| Incompatibility (Materials to Avoid) | N/A | | | |
| Hazardous Decomposition or Byproducts | Thermal decomposition may form carbon monoxide and carbon dioxide. | | | |

| SECTION VI(a) - Health Hazard Data | | | |
|--|--|---|-----------------------|
| Inhalation | May cause irritation. | | |
| Eye | Contact of the liquid with eyes will cause irritation. | | |
| Skin | May cause irritation. | | |
| Ingestion | Causes irritation. | | |
| Reported As Potential Carcinogen or Carcinogen | | | |
| | International Agency for Research on Cancer | X | Not Applicable |
| | National Toxicology Program | | OSHA |
| SECTION VI(b) - First Aid Procedures | | | |
| Inhalation | Remove victim to fresh air. If breathing has stopped, perform artificial respiration. Get medical attention. | | |
| Eye | Immediately flush eyes with plenty of water for at least 15 minutes, while holding eyelids open. Get medical attention. | | |
| Skin | Wash thoroughly with soap and water for at least 15 minutes. Remove contaminated clothing. Get medical attention. | | |
| Ingestion | DO NOT induce vomiting. If victim is conscious and alert, give large quantities of water. Get medical attention. | | |
| SECTION VI(c) - Employee Protection | | | |
| Respiratory Protection (Utilize NIOSH approved respirators when exposure levels exceed permissible limits. Refer to manufacturer's protection factors and OSHA standard 1910.134 as a guideline.) If TLV of product is exceeded, use NIOSH approved respirator, fully enclosed. | | | |
| <u>SPECIAL PROTECTION INFORMATION:</u> | | | |
| EYE | Chemical safety goggles or full face shield required if eye contact is possible. | | |
| SKIN | Chemical resistant gloves required, natural and butyl rubber gloves suggested. | | |
| VENTILATION | Provide sufficient mechanical ventilation to maintain exposure below TLV's. | | |
| SPECIAL PROTECTION | Impervious clothing and boots may be worn to prevent skin contact. Showers and eyewash facilities should be in close proximity. | | |
| SECTION VII - Special Precautions | | | |
| Handling and Storage | Store in dry, cool area, below 120°F and above 40°F. Do not store in metal containers. Excessive heat may cause pressure build-up. | | |
| Other Precautions | Not applicable. | | |
| SECTION VIII - Environmental Protection | | | |
| Spills / Releases | Trained personnel wearing protective equipment should contain spill. Spilled material will cause slippery contact surfaces. Scoop up or soak up and wash site. | | |
| Waste Disposal Method | In accordance with applicable local, state and federal regulations. | | |

DISCLAIMER

The information contained herein is based upon data available to us and reflects our best professional judgement. Since it is impossible to anticipate the conditions under which our products may be used, we cannot guarantee that the recommendations will be adequate for all individuals and situations. Each user of this product should determine the suitability of the product for his particular purpose and should comply with all federal, state and local regulations. Our goal is to manufacture products with zero or minimal hazards. Our products are improved daily as up-to-date information and research is received from our suppliers to use products with less or no hazards. Please feel free to contact us for current information.