

- \* Highly Concentrated
- \* Accelerated Catalytic Biodegradation
- \* Blend of Eight Selectively Adapted Strains
- \* Nonpathogenic Bacteria / Safe
- \* Reduces Maintenance Costs

# BREAK DOWN



## Grease Trap Treatment Compound # 9706

**CAUTION:** Avoid contact with eyes and skin.  
Do not inhale or ingest.

Eyes, Ingestion: exposure will cause irritation.

Skin, Inhalation: overexposure may cause irritation or allergic reactions.

Organisms used are nonpathogenic but can cause infection when in contact with open wounds. These organisms are susceptible to many commonly-used antibiotics.

### FIRST AID

Eyes or Skin: Flush with large amounts of water for 15 minutes. Launder contaminated clothes before reuse.

Inhalation: Remove victim to fresh air.

Ingestion: Drink water or milk to dilute. Induce vomiting only if advised by physician or poison control center.

If any irritation persists, seek immediate medical attention.

**BREAK DOWN** is a concentrated blend of multi-strain culture series selectively adapted to offer a broad spectrum of organic degradation capabilities. The strains are chosen for accelerated biodegradation of grease, fats, proteins, starch, sugars, oils, and cellulose, thus eliminating the accumulation of organic wastes on site. As regulations have become tighter, waste disposal more costly and grease trap requirements stricter, **BREAK DOWN** has been developed to effectively accelerate nature's own sanitation processes safely and to solve the organic waste problems of the food industry maintenance departments.

Application areas include industrial and institutional grease trap maintenance, industrial and municipal waste water treatment, waste containment lagoon treatment, line and trap treatment for food processing plants, meat plants and markets, restaurants, cafeterias, hotels, motels, hospitals, nursing homes, jails and virtually any facility with food processing and/or preparation operations.

### FOR COMMERCIAL OR INDUSTRIAL USE ONLY KEEP OUT OF REACH OF CHILDREN

? 1 Qt.(0.946L) ? 1 Gal.(3.785L) ? 5 Gal.(18.9L) ? 55 Gal.(208L)

### Application:

For optimum results, an initial "slurry" of two gallons should be applied directly to a freshly pumped grease trap to create a "bio-mass". Surface area must be moist for degradation activity. After the initial treatment, the product is to be applied daily, by a timed injector pump. This pump should be connected to the main line leading directly to the grease trap. For an average 500-1000 gallon grease trap, add 16-20 oz. of **BREAK DOWN** each day, always at the end of the work day to allow uninterrupted degradation activity. Use amounts depend on the volume and the severity of the organic waste problem as well as the performance quality desired.

For preventive maintenance and to eliminate garbage area odors, add 1-2 oz. to the drain or tank or spray 2-4 oz. onto the dumpster, respectively.

Do not mix with any chemicals. Keep product from contaminants.

Store containers in shaded area away from direct heat. For best results, storage temperature should be maintained between 40-110°F. Keep from freezing.